

REPORT

13 Series - Yesly



finder[®]
SWITCH TO THE FUTURE



YESLY TIME FOR COMFORT LIVING



The multifunction relays with Bluetooth represents the natural evolution of the traditional step relay; and thanks to its unparalleled flexibility. It can carry out a variety of ON/OFF functions associated with lighting, electric shutters or power curtains.

Features

- Type 13.72: integrates within most popular wall boxes, compatible with the most popular Italian wall switch systems
- Type 13.22 and 13.S2: round wall box (ie: Ø 60 mm) mounting
- Type 13.S2: single function relay (actuator) with Bluetooth suitable for electric roller blinds and shutters
- App programming/controlling with iOS or Android Smartphone
- Secure Bluetooth 4.2 Low Energy connection with 128-bit encryption



Type 13.72 - Multifunction relay compatible with the most popular Italian wall switch systems



Integrates within most popular wall boxes



Turning devices ON / OFF



Timer Settings




Electric roller blinds and shutter control




Type 13.72.8.230.B000 - white
Type 13.72.8.230.B002 - anthracite

- 2 independent and programmable channels
- 21 available functions ¹
- Default function (both channels): RI – Step relay (pushbutton control)
- 2 outputs with NO contacts rated 6 A 230 V AC
- Lamp load: 200 W 230 VAC
- 2 inputs for wired pushbuttons (one input per channel).
Up to 5 illuminated pushbuttons per input.
Can be managed through standard pushbuttons, wireless buttons, smartphone
- Management of up to 8 scenarios
- App programming with iOS or Android Smartphone
- Supply voltage 230 V AC (50/60 Hz)
- Secure Bluetooth 4.2 Low Energy connection with 128-bit encryption
- Compatible with the most popular Italian wall switch systems ²

² The Type 13.72 is compatible with most popular residential and commercial frame systems such as: AVE[®], Bticino[®], Gewiss[®], Simon Urmet[®], Vimar[®], through the use of special adaptors included in the box.



* Note: that these trademarks and trade names are not the property of Finder SpA or any of its associated companies, and are referred to in this sheet for the purposes of technical information only.



1 Selectable functions

- Monostable relay
- Step relay (RI - pushbutton control)
- Step relay (RIa - switch control, Type 13.22 only)
- Asymmetric flasher (starting pulse on) with control signal
- Interval with control signal on
- Interval with timed control signal
- Staircase light timer
- Staircase light timer + stair maintenance
- Staircase light timer with switch off early warning


- Staircase light timer with switch off early warning + staircase maintenance
- Timing step relay
- Timing step relay with switch off early warning
- Roller blind control (Type 13.72 only)
- Bathroom light and fan control
- Doorbell and light control
- 7 step relay sequences (see table)

Type	Functions	Sequences			
		1	2	3	4
13.22 13.72	02				
	03				
	04				
	05				
	06				
	07				
	08				


Examples of applications

Function TP - Roller Blinds, Shutters and Curtains


Ch1-P1: up
Ch2-P2: down



Function VB - Bathroom light + fan



Function CP - Doorbell + Lights





YESLY 13 SERIES - Multifunction relay with Bluetooth



Type 13.22 - Multifunction relay, round wall box (ie: Ø 60 mm) mounting



Wall box mounting



Turning devices ON / OFF




Timer Settings




Type 13.22.8.230.B000

The 13.22 is suitable for fitting within a 60mm round wall box or other junction boxes.




- 2 independent and programmable channels
- 21 available functions ¹
- Default function (both channels): RI – Step relay (pushbutton control)
- Special function RIa - Step relay (switch control). Ideal for converting a traditional system using one, two, or four way switches, into a Smart system
- 2 outputs with NO contacts rated 6 A 230 V AC
- Lamp load: 200 W 230 V AC
- 2 inputs for wired pushbuttons (one input per channel). Can be managed through standard wired pushbuttons, wireless pushbuttons, or Smartphone
- Management of up to 8 scenarios
- App programming with iOS or Android Smartphone
- Supply voltage 230 V AC (50/60 Hz)
- Secure Bluetooth 4.2 Low Energy connection with 128-bit encryption
- Round wall box (ie: Ø 60 mm) mounting



Examples of applications

Function VB - Bathroom light + fan





Special function RIa - Step relay (switch control). Ideal for converting a traditional system using one, two, or four way switches, into a Smart system


The Smart system controls from just a momentary push to a wired, wireless or Smartphone pushbutton



Function CP - Doorbell + Lights



Traditional installation



A Smart installation



Type 13.S2

Single function relay (actuator) with Bluetooth suitable for electric roller blinds and shutters



Wall box mounting





Electric roller blinds and shutter control



Type 13.S2.8.230.B000

- 1 specific function - Electric roller blinds and shutter control
- 2 outputs with NO contacts rated 6 A 230 V AC
- Motor load: 200 W 230 VAC
- 2 inputs for wired pushbuttons (one input per channel).
Up to 5 illuminated pushbuttons per input.
Can be managed through standard wired pushbuttons, wireless pushbuttons or Smartphone
- Management of up to 8 scenarios
- Programmable with iOS or Android Smartphone
- Supply voltage 230 V AC (50/60 Hz)
- Secure Bluetooth 4.2 Low Energy connection with 128-bit encryption
- Round wall box (ie: Ø 60 mm) mounting


The 13.S2 is suitable for fitting within a 60mm round wall box or other junction boxes.



Examples of applications

Function TP - Roller Blinds, Shutters and Curtains

Ch1-P1: up
Ch2-P2: down



FINDER reserves the right to alter characteristics at any time without notice. FINDER assumes no liability for damage to persons or property, caused as a result of the incorrect use or application of its products.

ADV13_YESLYEN-VII/2019 - Report 13 Series YESLY