




1Y.GW.8.230.BS00 **SMART HOME GATEWAY** 



# **WORKS WITH**

YESLY BLISS2















# **ENGLISH**

1Y.GW.8.230.BS00 MODULAR GATEWAY Wi-Fi 2.4 GHz - Radio 868 MHz

### 1 INSTALLATION

Install the gateway on DIN rail and connect live and neutral. After switching on, the Gateway's white LED will flash with a fading white light, awaiting configuration.

Use the **FINDER YOU** app both for configuring the BLISS2 smart chronothermostat and for YESLY systems.

For more information scan the OR code below.

# 2 STATUS LED

### WHITE LED

- Flashing fading: waiting for configuration
- Fixed: connection established with both the Wi-Fi network and the Cloud
- 2 flashes: connected only to the Wi-Fi network no connection to the Cloud (internet not active)
- 3 flashes: no connection to the Wi-Fi network and no connection to the Cloud (internet not active)

### **BLUE LED**

Flashing: sending Bluetooth commands to the devices **RED LED** 

Flashing: commands are sent to the Smart Bliss2 thermostat and actuators

## **G** GATEWAY SETTING

To change the light intensity of the white LED of the GATEWAY:

- press the button once: Low brightness
- press the button twice: Medium-Low brightness
- press the button 3 times: Medium-High brightness
- press the button 4 times: High brightness

### RESET

Press the button for > 10 seconds to reset the settings to factory REBOOT

Press to remove and return supply to the gateway

**MANUAL FINDER YOU** 

