

Contactores industriales



Nueva gama de contactores industriales













Serie 6K

Compactos y alto rendimiento

- CE

UK
CA

(según los tipos)

 	 	 	 
Tipo 6K.04.x.xxx.4x09 - 9 A - 400 V AC3 - 4 kW - 400 V AC3 Tipo 6K.04.x.xxx.4x12 - 12 A - 400 V AC3 - 5.5 kW - 400 V AC3 Tensiones disponibles: 24, 110, 230 V AC, 24 V DC	Tipo 6K.14.x.xxx.4x10 - 10 A - 400 V AC3 - 4 kW - 400 V AC3 Tipo 6K.14.x.xxx.4x18 - 18 A - 400 V AC3 - 7.5 kW - 400 V AC3 Tensiones disponibles: 24, 110, 230 V AC	Tipo 6K.13.8.xxx.4324 - 24 A - 400 V AC3 - 11 kW - 400 V AC3 Tipo 6K.13.8.xxx.4332 - 32 A - 400 V AC3 - 15 kW - 400 V AC3 Tensiones disponibles: 24, 110, 230 V AC	Tipo 6K.13.8.xxx.4350 - 50 A - 400 V AC3 - 22 kW - 400 V AC3 Tipo 6K.13.8.xxx.4374 - 74 A - 400 V AC3 - 37 kW - 400 V AC3 Tensiones disponibles: 24, 110, 230 V AC
3 NA + 1 NC  (47xx) 3 NA + 1 NA  (48xx) 4 NA  (43xx)	3 NA + 1 NC  (47xx) 3 NA + 1 NA  (48xx) 4 NO  (43xx)	3 NA 	3 NA 
Módulos auxiliares Contactos mecánicamente ligados conforme a la EN 60947-5-1, IEC 947-5-1			
Tipo 06K.03 para Tipo 6K.04 1 NO + 1 NC Tipo 06K.06 para Tipo 6K.04 2 NO + 2 NC 2 A (AC15 – 400 V) 	Tipo 06K.11 para Tipo 6K.13 y 6K.14 1 NO 2 A (AC15 – 400 V) 	Tipo 06K.12 para Tipo 6K.13 y 6K.14 1 NC 2 A (AC15 – 400 V) 	